

N. DROUCHE, H. MAHMOUDI, N. MAMERI, H. LOUNICI, N. GHAF FOUR

Utilization of electro dialysis for the regeneration of granular activated carbon packed in beds saturated with H₂S

Desalination, Volume **200**, Issues 1-3, 20 November 2006, Pages 629-631;

<http://dx.doi.org/10.1016/j.desal.2006.03.465>

ABSTRACT:

Olive oil production results in important quantities of wastewater containing large amounts of total solids and organic carbon as well as low oil concentrations. This paper describes the treatment of olive mill wastewater (OMW) by combining an ultrafiltration (UF) technique and an advanced oxidation process (AOP) using UV/H₂O₂. It further demonstrates the technical feasibility of this compact and stable process to remove a large part of total solids and organic carbon. Indeed, UF reduces the pollutants contained in the OMW with an apparent rejection coefficient R_{COD} in the range of 94%. The UV/H₂O₂ oxidation process may be easily used, in combination with UF, to finish the treatment of the permeate. The results obtained in batch and continuous mode showed that this technique offered a treated solution which complies with legal requirements. A final concentration of 17 mgTOC dm⁻³ was obtained, which corresponds to a final COD of 52 mg dm⁻³, while the legal requirement is 125. Furthermore, the final effluent is fully decolorized.